
PIPE CLAMP

two pieces with elastomer inlay







SOUND INSULATED according to DIN 4109

All dimensions in mm

Permissible tensile strength* in kg

Material b x s [mm]	until nominal diameter						
	40	100	400	500	700	1000	1400
20x1,5	60						
20x2,0		100	60	45	30		
30x2,5		180	130	115	90	70	40
40x4,0		320	240	220	160	140	80

 $^{^{\}star}$ valid for ceiling mounting usage only with tube types who do not deform themselves at mentioned load factors.

Description

Two pieces pipe clamp made from zinc-coated band steel or stainless steel quality A2 or A4. Suitable for all pipe types.

The connection to the structure is either via threaded rods at both limbs or via band steel at one limb.

Deliverable in diameter range from 15 mm until 1400 mm.

Preferable fields of application

Air-, climate-, sanitary- and heating technology

Specification

Zinc-coated, stainless steel material No. 1.4301 or 1.4571

Also STAINLESS available RUST PROOF

Material b x s	øD	L	d
20x1,5	15.0 17.2 consecutive pipe diameter until 38.0	20	6,5
20x2,0	42.0 42.4 consecutive pipe diameter until 710.0	20	6,5
30x2,5	48.3 50.0 consecutive pipe diameter until 1400.0	30	11,0
40x4,0	80.0 88.9 consecutive pipe diameter until 1400.0	40	13,0

Other diameters on request. Please tell us the requested pipe diameter.

08.17