


## SCREW-ON PIPE CLAMP

two pieces





All dimensions in mm

| Material<br>b x s   | øD   | L  | d   | Threaded<br>connection<br>Gw | Permissible tensile strength*<br>[kg]   |
|---|--|----|-----|------------------------------|---|
| 20x1,5  | 15.0<br>17.2<br>consecutive pipe<br>diameter until<br>38.0 | 18 | M 6 | M 8                          | 150   |
| 20x2,0  | 42.0<br>42.4<br>consecutive pipe<br>diameter until<br>60.3 | 18 | M 6 | M 8                          | 250   |
| Other diameters on request.<br>Please tell us the requested<br>pipe diameter. |  |    |     |                              | * valid for ceiling mounting usage only with<br>tube types who do not deform themselves at<br>mentioned load factors. |

## Description

58

Two pieces pipe clamp made from zinc-coated band steel or stainless steel quality A2 or A4. Embedded in the nut case is a threaded bolt for direct mounting to dowel, insulation units, helped track and others. The clamp connection screws, punched at the limbs, enable an easy mounting.

**Combination possibilities with Type** 

102a, 114 Mu and 114 Ni

**Preferable fields of application** 

Sanitary- and heating technology

Also STAINLESS available RUST PROOF